



SAFETY JOGGER

PROFESSIONAL



Light

ALIZA OB

Sandal in stretchable lycra

Our ALIZA sandal offer ESD protection, feature a stretchable upper, a removable footbed, superior body posture support and excellent grip. Ideal for various industries, these vegan shoes ensure cool, comfortable feet.

Upper	Lorica
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Phylon/Rubber (NBR)
Category	OB / ESD, A, SRC, E
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.231 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012



WHT



FUC




LBL



LLC



LMG



Stretchable upper

Super elastic and stretchable textile for improved comfort and fit.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

SAFETY
JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:
Catering, Cleaning, Food & beverages, Medical

Environments:
Dry environment, Extreme slippery surfaces

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Lorica			
	Upper: permeability to water vapor	mg/cm²/h	27.6	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	221	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm²/h	40.4	≥ 2
	Lining: water vapor coefficient	mg/cm²	325	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Phylon/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	118	≤ 150
	Outsole slip resistance SRA: heel	friction	0.37	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.37	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.19	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.23	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	51	0.1 - 100
	Heel energy absorption	J	28	≥ 20

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.